


PIN	SYMBOL
1	DB0
2	DB1
3	DB2
4	DB3
5	DB4
6	DB5
7	DB6
8	DB7
9	RD
10	CS
11	WR
12	GND
13	TE
14	RS
15	LEDA
16	IOVCC
17	VCC
18	LEDK
19	RESET
20	GND

NOTES:

1. VIEWING DIRECTION FREE
2. POLARIZER MODE : TRANSMISSIVE
3. OPERATING TEMP : -10°C~+60°C
4. STORAGE TEMP : -20°C~+70°C
5. DRIVER IC : ST7789V2
6. CONNECTOR : COG+FPC
7. GENERAL TOLERANCE ±0.2



Backlight Circuit
I=30mA(Type)/40mA(Max)
VF=3.0V(Type)

东莞市方胜电子有限公司
DONGGUAN FANGSHENG ELECTRONIC., LTD

REV	DESCRIPTION	DATE	SCALE: 1/1	UNIT: mm	PAGE: 1/1	APPROVED	CHECKER	DRAWN
A	THE FIRST ISSUE	2020.3.10						
B	按客户需求改接口定义	2020.4.3						
C	改FPC出pin位置 和结构 FPC定为20pin	2020.4.6						
E	FPC加长2mm	2020.6.6						

JPY13003-20P		ED1	0.1	2020.02.27
--------------	--	-----	-----	------------

由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作